

**Amendments to the Claims:**

This listing of claims will replace all prior versions, and listings, of claims in the application:

**Listing of Claims:**

1. (currently amended) A vascular occlusion coil deployment system for use in placing a coil at a preselected site within a vessel comprising:

an elongated flexible positioning member having a lumen extending therethrough and having proximal and distal ends;

an embolic coil;

an elongated flexible delivery member having a lumen extending therethrough and being positioned within the lumen of the positioning member and having proximal and distal ends;

a heating element mounted on the distal end of the delivery member, said heating element being an electrically heated coil;

a non-optical energy transmission conductor extending along the lumen of the delivery member and extending from the proximal end to the distal end of the delivery member, said energy transmission conductor being coupled to said heating element; and,

a unitary non-metallic heat responsive coupling member coupled directly to the heating element coil and normally retaining the embolic coil by an adhesive bond, said heat responsive coupling member comprises a biocompatible adhesive that exhibits the characteristic of, upon being heated, releasing the adhesive bond and the embolic coil at the preselected site, and wherein the yield strength of the biocompatible adhesive is reduced when heated by the heating element.

2. (cancelled)

3. (currently amended) A vascular occlusion coil deployment system as defined in claim 21, wherein said adhesive is a hot melt adhesive that is bonded to the embolic coil prior to exhibiting said characteristic of releasing upon being heated and wherein the yield strength is reduced at least 50 percent when heated to about 65 degrees Celsius.

4. (previously presented) A vascular occlusion coil deployment system as defined in claim 1, wherein said adhesive is a hot melt adhesive polymer.

5. (previously presented) A vascular occlusion coil deployment system as defined in claim 4, wherein the hot melt adhesive, upon being heated, softens so that it may be stretched to release the adhesive bond.

6. (previously presented) A vascular occlusion coil deployment system as defined in claim 5, wherein said hot melt adhesive has a lower yield strength, upon being heated, than prior to being heated.

7. (previously presented) A vascular occlusion coil deployment system as defined in claim 5, wherein said hot melt adhesive softens so that it may be stretched upon being heated to at least about 63 degrees Celsius.

8. (previously presented) A vascular occlusion coil deployment

system as defined in claim 1, wherein said adhesive bond of the heat responsive coupling member, upon being heated, breaks when said delivery member is retracted with respect to said positioning member to release said embolic coil.

9. (previously presented) A vascular occlusion coil deployment system as defined in claim 8, wherein the release of said embolic coil comprises disengaging said heating element from said embolic coil by breaking said adhesive bond.